


liquid cement screed



## Key benefits

Longfloor IntegraCure<sup>®</sup> is the perfect liquid cement screed for both domestic and commercial use flooring:

With all other cement based flowing screed systems, a curing agent is required to stop the material drying out too quickly, which can result in plastic shrinkage cracking. IntegraCure® completely removes this process from the installation of the screed.

Dries in  $\frac{1}{3}$  of the time of a traditional sand/cement screed or standard anhydrite flowing screeds.

Allows foot traffic in just 24-48 hours after placing.

Suitable to receive non-moisture sensitive floor finishes between 7-14 days.

Laitance free – meaning there's no site revisits for sanding.



1990年11月1日 1990年11日

On a single visit over 1000m<sup>2</sup> can easily be laid.

Compatible with all types of primers, grouts and adhesives and can even be laid in wet rooms.

Excellent thermal conductivity ranging from 1.9W/m.K to 2.6W/m.K dependent on raw material package.

Maximum bay sizes can now be between 200-250m<sup>2</sup> dependent on length to width ratio and room shape. Aspect ratio can now exceed 4:1

25N/mm<sup>2</sup> compressive strength and 6N/mm<sup>2</sup> flexural strength. Higher strength versions are available upon request.

Drying shrinkage is significantly reduced compared to other cementitious systems.

Longfloor IntegraCure® binder contains 95% recycled material as verified under ISO 14021.

Longfloor IntegraCure® is a truly innovative and game-changing material.





Longcliffe Quarries Ltd Brassington, Matlock, Derbyshire DE4 4HN

Tel: 01629 540284 Fax: 01629 540569 Email: Sales@longfloor.co.uk www.longfloor.co.uk

Registered No. 00273400